Document made available under **Patent Cooperation Treaty (PCT)**

International application number: PCT/GB05/000078

International filing date:

12 January 2005 (12.01.2005)

Document type:

Certified copy of priority document

Document details:

Country/Office: GB

Number:

0401053.4

Filing date:

17 January 2004 (17.01.2004)

Date of receipt at the International Bureau: 09 February 2005 (09.02.2005)

Remark:

Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse





PCT/GB2005/00078

The Patent Office Concept House Cardiff Road Newport South Wales NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subject the company to certain additional company law rules.

Signed

Dated 21 January 2005

An Executive Agency of the Department of Trade and Industry

Patents Form 1/77



1 7 JAN 2004

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road Newport Gwent NP9 1RH

1. Your reference

QIP/P7336

2. Patent application number (The Patent Office will fill in this part)

0401053.4

19JAN04 EB66338-1 D02776______P01/7700 0.00-0401053.4 ACCOUNT CHA

3. Full name, address and postcode of the or of each applicant (underline all surnames)

QINETIQ LIMITED

Registered Office 85 Buckingham Gate

London SW1E 6PD United Kingdom

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

08527376002

GB

4. Title of the invention

Improvements in and relating to accelerometers

Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Ian Michael Johnson

QINETIQ LIMITED
IP Formalities
A4 Bldg

Cody Technology Park Ively Road

Farnborough
Hants GU14 0LX United Kingdom

Patents ADP number (if you know it)

08183873001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number Country

Piority application number (if you know it)

Date of filing (day/month/year)

 If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application Number or earlier application

Date of filing (day/month/year)

8. Is a statement of inventorship and of right if to grant of a patent required in support of this request? (Answer 'Yes' if:

a) any applicant named in part 3 is not an inventor, or

YES

there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body. See note (d))

Patents Form 1/77

Patents Form 1/77

Penter the number of sheets for any of the lowing items you are filing with this form. To not count copies of the same document

Continuation sheets of this form

Description 4

Claim(s) 1

Abstract 1

Drawing(s) 2 ^

4

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination 1 and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

I.M. Johnson, Agent for the Applicant

Date: 16.01.2004

12. Name and daytime telephone number of person to contact in the United Kingdom


Mrs Linda Bruckshaw 01252 392722


Warning


After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent of the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have attached 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.







Spere

Improvements in and relating to accelerometers

The present invention relates to accelerometers and particularly fibre optic accelerometers for use in interferometers.

10

15

20

30

The need to monitor extremely low levels of vibration in areas such as security, seismic survey and condition monitoring of machinery and such like has spurred the development of ever more sensitive accelerometers. Fibre optic technology has been applied to this particular field in the form of fibre-optic accelerometers based on interferometric techniques. The compliant cylinder approach to the design of a fibre-optic accelerometer is particularly effective when incorporated in such an interferometer. In one known approach a seismic mass is held in place by two compliant cylinders and around the circumference of each cylinder there being wound a single mode optical fibre, which form the arms of an interferometer. In another approach, a single compliant cylinder 2 loaded with a seismic mass 4 as shown in Figure 1 is wound circumferentially with an optical fibre 6.

Whilst the abovementioned approaches have found acceptance, there remains a need to increase yet further the sensitivity of the accelerometer beyond that currently achievable and in particular to do so without any increase in component size. The present invention seeks to improve the sensitivity of a fibre wound compliant cylinder accelerometer whilst simultaneously seeking to avoid additional cost and complexity of construction.

Thus, according to one aspect of the invention, there is provided a fibre optic 25 accelerometer comprising a seismic mass coaxially constrained within a cylinder of compliant material, the cylinder being circumferentially wound with optical fibre.

Preferably, the accelerometer is mounted on a plate which may or may not in practice be an integral part of a platform or structure on which the accelerometer is deployed. Conveniently, a tension member retains the accelerometer against the plate. The tension member may be a bolt or other well known tensioning component. Equally, the tension member may be provided by an enclosure or can acting on the accelerometer. Advantageously, the tension member acts on the accelerometer via a compliant material washer whilst a rigid support ring is interposed between the plate and the cylinder to 35 ensure that relative movement is possible.

It will be recognised that a suitable compliant material for the cylinder will have a relatively low Young's modulus but with a Poisson's ratio close to 0.5, such that the stiffness of the accelerometer arises more from the circumferential winding than the cylinder itself. Thus for a particular force acting on the cylinder, the greater the strain induced in the fibre and hence sensitivity of the accelerometer. Furthermore, by constraining the seismic mass coaxially within the cylinder, the tendency present in prior art devices for the cylinder to buckle or otherwise respond unfavourably to acceleration orthogonal to the cylinder axis is limited. Advantageously, this leads to improved performance of devices incorporating the accelerometer in which sensitivity in a single axis is paramount.

It will be further recognised that by reducing the wall thickness of the cylinder the sensitivity of the accelerometer can be still further increased. Prior art devices have hitherto sought to increase sensitivity either by increasing the seismic mass and/or the height of the cylinder supporting the seismic mass. Both approaches whilst increasing the desired sensitivity may also have the problem of increased sensitivity to orthogonal acceleration mentioned above and will result in an increased accelerometer size. With the trend towards miniaturisation of components, the present invention lends itself to providing improved performance to prior art devices for a given volume and mass.

In order to assist in understanding the invention, a particular embodiment thereof will now be described, by way of example and with reference to the accompanying drawings, in which:

25

35

20

10

15

Figure 1 is a cross-sectional side view of a prior art fibre optic accelerometer;
Figure 2 is a cross-sectional side view of a fibre optic accelerometer in accordance with the present invention; and

Figure 3 is a schematic view of an optical interferometer incorporating an accelerometer of Figure 2.

The fibre optic accelerometer 1 is mounted on a base plate 3 via a rigid support ring 5. The ring 5 can be formed either as a relief in the base plate 3 or perhaps more conveniently, it can be provided as a separate component, thereby allowing differing sizes of accelerometer 1 to be mounted on the base plate 3. The base plate 3 itself is produced from a rigid material, typically steel although other metals and composites may suggest themselves to those skilled in the art. Furthermore, it should be understood that

references throughout the description to a base plate are also intended to encompass the direct mounting of the accelerometer to a platform or other structure.

The support ring 5 is in contact with a first end face of a compliant cylindrical member 7. The cylindrical member has relatively thin wall 9 and a coaxial void 11 such that a seismic mass 13 may be received therein. The compliant cylindrical member 7 is formed from a material having a relatively low Young's modulus such that it is capable of deformation under low levels of loading in an axial direction. Typically, a rubber or rubber like material may be utilised. Such materials also have a Poisson ratio approaching a maximum of 0.5 meaning that an efficient transfer of axial deformation into circumferential deformation in the cylinder 7 can take place.

10

15

20

25

30

35

The seismic mass 13 is held by a tension member in the form of a bolt 15 secured to the base plate 3. Whilst in a non-illustrated embodiment the tension member is provided by an enclosure or can, other forms of tension member will be readily apparent to those skilled in the art. The bolt 15 bears on the seismic mass 13 via an elastomeric member which is most easily provided by a pad 17 of rubber of rubber-like material. The seismic mass 13 itself is so shaped that a generally disc shaped portion 19 bears on a second end face 21 of the compliant cylindrical member 7. In use, acceleration forces acting on the seismic mass 13 bring about a displacement which is coupled to the cylindrical member 7. Without the tension member 15, there would be no coupling of displacement to the cylindrical member 7 where the sense of acceleration is such as to urge the disc shaped portion 19 out of contact with the second end face 21. In effect, the tension member 15 preloads the cylindrical member 7 with an initial displacement. Depending on the range of acceleration expected, the preload may be varied by altering the level of tension provided by the tension member 15.

The cylindrical member 7 is wound with a length of optical fibre 23. The winding may be single or multi layered. The optical fibre 23 is wound about an external surface 25 of the cylinder 7 and may be secured mechanically, adhesively or through another or combination of techniques to ensure that as completely as possible the possibility of slippage between the fibre 23 and the cylinder surface 25 is minimised.

It will be appreciated that the optical fibre 23 constrains the cylindrical member 7 against circumferential deformation thus generating a level of hoop stress in the fibre 23. This hoop stress alters the physical characteristics of the optical fibre 23 such that by incorporating the accelerometer in one arm of an optical interferometer (Figure 3) a

stress value proportional to the acceleration acting on the accelerometer 1 can be determined.

5 Figure 3 shows the accelerometer 1 as an element in an optical interferometer 30 used to determine acceleration. In this embodiment there is provided a source of laser light 31 a coupler 32, coupling two arms 33,34 of fibre optic cable and an output to a display 35. One of the arms 33 contains the accelerometer 1 whilst the other arm 34 includes a polarisation corrector 36. The operation of such an interferometer 30 will be apparent to those skilled in that art just as those skilled in the art will recognise that this interferometer is purely illustrative and that the accelerometer of the invention may be deployed in a host of interferometer applications.

Whilst those skilled in the art will recognise the improvements in resistance to off-axis acceleration effects conferred by the above described embodiment, further steps may be taken to minimise the detrimental effect of such inputs. Accordingly, a shim may be added between the tension member and the cylinder to resist out of axis inputs whilst maintaining on-axis sensitivity.

15

Claims

20

- A fibre optic accelerometer comprising a seismic mass coaxially constrained within a cylinder of compliant material, the cylinder being circumferentially wound with optical fibre.
- 2. An accelerometer as claimed in Claim 1, wherein the seismic mass is surmounted with a disc shaped portion.
 - 3. An accelerometer as claimed in Claim 1 or Claim 2, wherein the seismic mass is secured by a tension member to a base plate.
- 4. An accelerometer as claimed in Claim 3, wherein a spacer is provided between the cylinder and the base plate.
 - An accelerometer as claimed in Claim 4, wherein the spacer is integral with the base plate.
 - An accelerometer as claimed in any preceding Claim, wherein the optical fibre is wound in a single layer.
- 7. An accelerometer as claimed in any preceding Claim, wherein the base plate is integral with a platform or structure.
 - 8. A fibre optic accelerometer substantially as described herein with reference to Figure 2 of the accompanying drawings.
- 9. A optical interferometer substantially as described herein with reference to Figure3 of the accompanying drawings.

Abstract

Improvements in and relating to accelerometers

A fibre optic accelerometer (1) particularly intended for use with an interferometer (30) is described. The accelerometer (1) utilises the compliant cylinder approach but through providing the seismic mass (13) at the core of the cylinder (7), this results in improved sensitivity and rejection of out of axis inputs.

(Figure 2)

15

5

10

PATENT COOPERATION TREATY

From the INTERNATIONAL BUREAU

PCT

NOTIFICATION CONCERNING SUBMISSION OR TRANSMITTAL OF PRIORITY DOCUMENT

(PCT Administrative Instructions, Section 411)

To:

TOCHER, A., J. QinetiQ Ltd, IP Formalities Cody Technology Park A4 Building, Room G016 Ively Road, Farnborough Hampshire GU14 0LX ROYAUME-UNI

Date of mailing (day/month/year) 14 March 2005 (14.03.2005)	
Applicant's or agent's file reference IP/P7336/WOD	IMPORTANT NOTIFICATION
International application No. PCT/GB05/000078	International filing date (day/month/year) 12 January 2005 (12.01.2005)
International publication date (day/month/year)	Priority date (day/month/year) 17 January 2004 (17.01.2004)
Applicant	INETIQ LIMITED et al

- 1. By means of this Form, which replaces any previously issued notification concerning submission or transmittal of priority documents, the applicant is hereby notified of the date of receipt by the International Bureau of the priority document(s) relating to all earlier application(s) whose priority is claimed. Unless otherwise indicated by the letters "NR", in the right-hand column or by an asterisk appearing next to a date of receipt, the priority document concerned was submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b).
- 2. (If applicable) The letters "NR" appearing in the right-hand column denote a priority document which, on the date of mailing of this Form, had not yet been received by the International Bureau under Rule 17.1(a) or (b). Where, under Rule 17.1(a), the priority document must be submitted by the applicant to the receiving Office or the International Bureau, but the applicant fails to submit the priority document within the applicable time limit under that Rule, the attention of the applicant is directed to Rule 17.1(c) which provides that no designated Office may disregard the priority claim concerned before giving the applicant an opportunity, upon entry into the national phase, to furnish the priority document within a time limit which is reasonable under the circumstances.
- 3. (If applicable) An asterisk (*) appearing next to a date of receipt, in the right-hand column, denotes a priority document submitted or transmitted to the International Bureau but not in compliance with Rule 17.1(a) or (b) (the priority document was received after the time limit prescribed in Rule 17.1(a) or the request to prepare and transmit the priority document was submitted to the receiving Office after the applicable time limit under Rule 17.1(b)). Even though the priority document was not furnished in compliance with Rule 17.1(a) or (b), the International Bureau will nevertheless transmit a copy of the document to the designated Offices, for their consideration. In case such a copy is not accepted by the designated Office as the priority document, Rule 17.1(c) provides that no designated Office may disregard the priority claim concerned before giving the applicant an opportunity, upon entry into the national phase, to furnish the priority document within a time limit which is reasonable under the circumstances.

Priority date Priority application No. Country or regional Office or PCT receiving Office of priority document

17 January 2004 (17.01.2004) 0401053.4 GB 09 February 2005 (09.02.2005)

The International Bureau of WIPO
34, chemin des Colombettes
1211 Geneva 20, Switzerland

Facsimile No. +41 22 740 14 35

Authorized officer

Vannier James

Facsimile No. +41 22 338 89 65
Telephone No. +41 22 338 8454